



KEY FEATURES :

- 10.4" Touch Screen
- Fast Charging
- Dual Gun CCS-2
- CMS Compatible
- Password Protected
- Emergency ON-OFF
- High Reliability & Stability
- Endurance Performance

APPLICATIONS :

Retail & Hospitality, Commercial, Residential, Fuel Retailers, Fleet Charging, Hotels, Resorts, Warehouse etc.

TECHNICAL SPECIFICATIONS :

Specifications	PIPL-60KEV
Output Characteristics	
Voltage	150VDC TO 1000VDC
Current	200Amp Max
Max Power	60KW [DUAL GUN 30KW+30KW]
Input Characteristics	
Input Voltage	360V TO 470VAC (415vac - 3Phase - 4Wire + Earth)
Frequency	47-63Hz
Efficiency	> 95%
Display & Communication	
Display	10.4" Touch Screen
Network Interface	LAN
Communication Protocol	OCPP1.6J
General	
Environment	Indoor / Outdoor
Operating Temperature	-20 to 60deg
IO Isolation	I/P to O/P : 1.5KV & I/P TO GND : 500VDC
Relative Humidity	≤95%, Non-Condensing
Cooling	Conventional Fan Cooled
Dimensions	900 (W) x 500 (D) x 2000 (H) mm

WE PURSUE A POLICY OF CONTINUOUS DEVELOPMENT AND PRODUCT IMPROVEMENT. THUS THE SPECIFICATIONS IN THIS DOCUMENTS AND THE LOCATION OF CONTROLS ON THE FRONT PANEL MAY BE CHANGE D WITHOUT NOTICE.

Apr 2022